


330±20

ELECTRICAL PROPERTIES:

100% OPEN SHORT MIS-WIRE TEST
 CONTACT RESISTANCE: 30HM MAX
 INSULATION RESISTANCE: 10MEGA OHM MIN
 HIPDT TEST: DC300V 10MS



PIN ASSIGNMENT

HSG	10P	1394	6P
1	_____	_____	5
2	_____	_____	6
3	_____	_____	SHELL 2
4	_____	_____	SHELL 1
5	_____	_____	3
6	_____	_____	4
7	_____	_____	1
8	_____	_____	—
9	_____	_____	2
10	_____	_____	—

10	PVC MOLDED COLDR: BEIGE		
9	HEAT SHRINK TUBING Ø1.5*28MM BLACK	4	PCS
8	HEAT SHRINK TUBING Ø5.0*12MM BLACK	2	PCS
7	NUT #4-40 4.79*1.9MM	4	PCS
6	SCREW #4-40 L: 6MM	4	PCS
5	TU5005 德?	16	PCS
4	HOUSING 2*5 PITCH 2.54MM COLDR: LIGHT BLUE	2	PCS
3	?? ?????(PORT)	1	PCS
2	1394 6P FEMALE WHITE PASTERN	2	PCS
1	UL20276 30#*2P+24#*2C L=315±2MM DD:5.3±0.15MM COLDR: BEIGE	2	PCS
ND.	DESCRIPTION	Q'TY	UNIT
A	CABLE 1394 6F*2 TD 2.54 HOUSING*2 L330MM		
REV.	DESCRIPTION	DATE	

UNLESS OTHERWISE SPECIFIED TOLERANCE

ANG. 0.0
 FRACTIONAL ±0.5
 DECIMAL ±0.2

SCALE: 1:1
 DRAWN REIC XU
 CHECKED

DUN CHENG TECH. CORP.
 TEL:886-2-26759970 FAX:886-2-26759980



DATE: 05/10/26
 APPROVED
 SIZE: A4
 REV: A
 PRODUCT NO.: E1394-6
 FILE NAME: E1394-6