



PIN ASSIGNMENT

1394 6P MALE	1	2	3	4	5	6	SHELL
1394 6P MALE	1	2	3	4	5	6	SHELL

ELECTRONIC TEST:

- 1.OPEN/SHORT/INTERMITTE:100%.
- 2.INSULATION RESISTANCE:10MΩ.
- 3.CONTACT RESISTANCE:100Ω.
- 4.THE WIRES THAT THEY WERE SOLDERED IN THE PIN #5 AND #6 OF THE 1394 6P MALE ARE THROUGH THE CORE.

4	INTERNAL WIRE:UL1007 30AWG 7 STRAND	PCS	6
3	CORE:18RID6.4mm*3.2mm*3.5mm	PCS	1
2	PVC MOLDED WITH BLACK IN COLOR		
1	1394 6P TYPE MALE SHELL PLATED:NICKEL CONTACT:G/F	PCS	2
NO.	DESCRIPTION	UNIT	QTY

TOLERANCE			
SELECT	1	2	3
DN TOL	0.00	0.02	0.05
0.00 +/-	0.02	0.05	0.10
0.00 +/-	0.05	0.10	0.15
0.00 +/-	0.10	0.15	0.20
0 +/-	0.15	0.20	1.00
ANGLE+/-	10'	10'	15'
MATERIAL			

UNLESS OTHERWISE SPECIFIED TOLERANCE
 ANG: 0°
 FOS ±0.5
 ±0.2

SCALE: 1:1 UNIT: mm

DRAWN My.Chen 02/15/05



DUN CHENG TECH. CORP.
 TEL:886-2-26739970 FAX:886-2-26739980

A	ADP-1394-6M6M	IEEE ADAPTER	IEEE 1394 ADAPTER 6PIN MALE TO 6PIN MALE MOLDED	02/15/05	APPROVED	SIZE A4	REV. A	PRODUCT NO. ADP-1394-6M6M
REV.			DESCRIPTION	DATE	CHECKED			FILE NAME: ADP-1394-6M6M

PRODUCT NO. ADP-1394-6M6M
 DRAWN NAME: ADP-1394-6M6M