



- NOTES:
- ELECTRICAL DATA  
 CURRENT: 15A  
 VOLTAGE: 30V  
 CONTACT RESISTANCE: 50MΩ  
 DIELECTRIC WITHSTAND: 100VDC  
 INSULATION RESISTANCE: 100MΩ MIN.
  - PHYSICAL DATA  
 HOUSING: BLACK GLASS FILLED 4/6 NYLON,UL94V-0  
 CONTACTS: PHOSPHOR BRONZE  
 PLATING: TIN/LEAD OVER NICKEL IN WIRE TERMINATION AREA  
 NICKEL UNDERPLATE ALL OVER.  
 PLATING ON MATING AREA PER PART NUMBER BREAKDOWN.  
 METAL SHELL: STEEL TIN/LEAD OVER NICKEL PLATING  
 TEMPERATURE: -40°C TO +85°C OPERATING  
 -40°C TO +105°C STORAGE
  - CABLE ASSEMBLY DESIGNED TO MEET THE ELECTRICAL, MECHANICAL AND ENVIRONMENTAL REQUIREMENTS OF THE IEEE-1394b SPECIFICATION.
  - ADAPTER COLOR: BLACK

NO.	DESCRIPTION	QTY
1	UL1007 30 AWG JUMPER WIRE	6PCS
2	1394 4P MALE	1SET
3	1394 9P BILINGUAL BLACK PASTERN CONNECTOR(OUTSIDE COVER: BLACK)	1SET
4	PVC SSP BLACK COLDR	

ADAPTER IEEE-1394B 9M BILINGUAL TO 4 MALE		DATE	06/09/03	APPROVED	SIZE	A4	REV.	A	FILE NAME:	ADP-1394B-9BL4M
DESCRIPTION				CHECKED				DRAWN NAME:		ADP-1394B-9BL4M
				DRAWN Merry_Pang				DATE		06/09/03
				SCALE: 1:1				UNIT:		MM
				UNLESS OTHERWISE SPECIFIED TOLERANCE						
				ANG:						
				0						
				±0.5						
				±0.3						
				±0.2						
				DUN CHENG TECH. CORP.						
				TEL:886-2-26739970 FAX:886-2-26739980						
				PRODUCT NO. ADP-1394B-9BL4M						
				ADP-1394B-9BL4M						