



stable rubber

ELECTRICAL PROPERTIES:

1. 100% OPEN SHORT MIS-WIRE TEST
2. Contact Resistance: 100ohm
3. Insulation Resistance: 5Mega ohm
4. HI-Pot: 300V DC/10ms

7	ABS ASS'Y BLACK IN COLOR	PCS	1
6	DC JACK<math>\phi 3.5 \times 1.0</math> SHELL PLATED NICKEL	PCS	1
5	MINI USB 4P MALE<math>(HROSE)</math> SHELL PLATED NICKEL CONTACT<math>G/F</math>	PCS	1
4	MINI USB 4P MALE<math>(MISTUM)</math> SHELL PLATED NICKEL CONTACT<math>G/F</math>	PCS	1
3	USB B TYPE MALE SHELL PLATED NICKEL CONTACT<math>G/F</math>	PCS	1
2	USB-A TYPE MALE INSULATION<math>BEIGE</math> IN COLOR	PCS	1
1	MINI USB B TYPE 5P FEMALE SHELL PLATED NICKEL CONTACT<math>G/F</math>	PCS	1
No.	DESCRIPTION	UNIT	Q'TY

DATE	07/12/11	APPROVED	SIZE	A4	REV.	A	FILE NAME:	PRODUCT NO.
UNLESS OTHERWISE SPECIFIED TOLERANCE		SCALE: NONE		UNIT: mm		DUN CHENG TECH. CORP., TEL:886-2-26739970 FAX:886-2-26739980		
ANG. 0° ±0.5						DRAWN NAME:		
0.0 ±0.3						DRAWN Xing Fa		
±0.2						CHECKED Eric		
						07/12/11		
						6INI-ADP-S55		

