



PIN ASSIGNMENT

1394 4P FEMALE	1	2	3	4	SHELL
1394 4P FEMALE	1	2	3	4	SHELL

ELECTRONIC TEST:
 1.OPEN/SHORT/INTERMITT:100%.
 2.INSULATION RESISTANCE:10MΩ.
 3.CONTACT RESISTANCE:100Ω.
 4.THE WIRES THAT THEY WERE SOLDERED
 IN THE PIN #1 AND #2 OF THE 1394 4P
 FEMALE ARE THROUGH THE CORE.

5	INTERNAL PC:BOARD:11.20MM*13.20MM*1.00MM PCB FOR 1394 4P FEMALE SMT	PCS	2
4	INTERNAL WIRE:UL1007 30AWG 7 STRAND L:17MM	PCS	4
3	CORE:F18RID6.4mm*3.2mm*3.5mm	PCS	1
2	PVC MOLDED WITH COPPER FOIL BEIGE IN COLOR		
1	1394 4P TYPE FEMALE SMT INSULATION:BLACK IN COLOR	PCS	2
ND.	DESCRIPTION	UNIT	QTY

TOLERANCE		SELECT		
DN	TOL	1	2	3
0.000	+/- .002	0.05	0.05	0.10
0.00	+/- .005	0.10	0.15	0.15
0.00	+/- .010	0.15	0.20	0.20
0	+/- .015	0.20	1.00	1.00
ANGLE:1.10°		1.0°	1.0°	1.5°

UNLESS OTHERWISE
 SPECIFIED TOLERANCE
 ANG: F0.5
 ±0.5
 ±0.2

SCALE: 1:1 UNIT: mm
 DRAWN MICHAEL 07/03/01
 CHECKED HENRY 07/03/01
 APPROVED JIMMY 07/03/01



DUN CHENG TECH. CORP.
 TEL:886-2-26739970 FAX:886-2-26739980

7800-0016

A	ADP-1394-4F4F	IEEE ADAPTER	IEEE 1394 ADAPTER 4PIN FEMALE TO 4PIN FEMALE MOLDED	07/03/01	DATE	SIZE	REV.	FILE NAME:
REV.			DESCRIPTION			A4	A	ADP-1394-4F4F