



PIN ASSIGNMENT

1394 6P FEMALE	1	2	3	4	5	6	SHELL
1394 6P FEMALE	1	2	3	4	5	6	SHELL

ELECTRONIC TEST:

- 1.OPEN/SHORT/INTERMITTE:100%.
- 2.INSULATION RESISTANCE:10MΩ.
- 3.CONTACT RESISTANCE:100Ω.
- 4.THE WIRES THAT THEY WERE SOLDERED IN THE PIN #5 AND #6 OF THE 1394 6P FEMALE ARE THROUGH THE CORE.

4	INTERNAL WIRE:UL1007 30AWG 7 STRAND L:17MM	PCS	6
3	CORE:F18RID6.4mm*3.2mm*3.5mm	PCS	1
2	PVC MOLDED WITH COPPER FOIL BEIGE IN COLOR	PCS	1
1	1394 6P TYPE FEMALE INSULATION:WHITE IN COLOR	PCS	1
NO.	DESCRIPTION	UNIT	QTY

TOLERANCE			
SELECT	1	2	3
DN	0.00	0.02	0.05
UP	0.00	0.02	0.05
ANGLE+/-	0	0.15	0.20
MATERIAL	1.0'	1.0'	1.5'

UNLESS OTHERWISE SPECIFIED TOLERANCE ANG: ±0.5 ±0.3 ±0.2



DUN CHENG TECH. CORP.
TEL:886-2-26739970 FAX:886-2-26739980

A	ADP-1394-6F6F	IEEE ADAPTER	IEEE 1394 ADAPTER 6PIN FEMALE TO 6PIN FEMALE MOLDED	07/03/01	DATE	SIZE	REV.	FILE NAME:
REV.			DESCRIPTION			A4	A	ADP-1394-6F6F

SCALE: 1:1
DRAWN MICHAEL 07/03/01
CHECKED HENRY 07/03/01
APPROVED JIMMY 07/03/01

PRODUCT NO. ADP-1394-6F6F
DRAWN NAME: ADP-1394-6F6F