


1394 6P MALE



1394 4P MALE

1394 6P MALE	5	6	3	4	SHELL
PIN ASSIGNMENT					
1394 4P MALE	1	2	3	4	SHELL

5	INTERNAL WIRE:UL1007 30AWG 7 STRAND L:30MM	PCS	4
4	CORE:F18RID6.4mm*3.2mm*3.5mm	PCS	1
3	1394 4P TYPE MALE INSULATION:BLACK IN COLDR	PCS	1
2	PVC MOLDED WITH COPPER FOIL BLACK IN COLDR	PCS	1
1	1394 6P TYPE MALE INSULATION:BLACK IN COLDR	PCS	1
NO.	DESCRIPTION	UNIT	QTY

ELECTRONIC TEST:

- 1.OPEN/SHORT/INTERMITTE:100%.
- 2.INSULATION RESISTANCE:10MΩ.
- 3.CONTACT RESISTANCE:100Ω.
- 4.THE WIRES THAT THEY ARE SOLDERED IN THE PIN #5 AND #6 OF THE 1394 6P MALE ARE THROUGH THE CORE.

TOLERANCE	
SELECT	✓
DN TOL	1 2 3
0.00 +/- 0.02	0.05 0.10
0.00 +/- 0.05	0.10 0.15
0.00 +/- 0.10	0.15 0.20
0 +/- 0.15	0.20 1.00
ANGLE: 10°	10° 15°
MATERIAL:	

UNLESS OTHERWISE SPECIFIED TOLERANCE  
 ANG: 0°  
 ±0.5  
 ±0.3  
 ±0.2

SCALE: 1:1  
 DRAWN MICHAEL 07/03/01  
 CHECKED HENRY 07/03/01  
 APPROVED JIMMY 07/03/01



DUN CHENG TECH. CORP.  
 TEL:886-2-26739970 FAX:886-2-26739980

REV.	A	ADP-1394-4M6M	IEEE ADAPTER	IEEE 1394 ADAPTER 4PIN MALE TO 6PIN MALE MOLDED	07/03/01	DATE	SIZE	REV.	FILE NAME:
							A4	A	ADP-1394-4M6M