


20M



ELECTRICAL PROPERTIES:

1. 100% OPEN SHDRT MIS-WIRE TEST
2. Contact Resistance: 10ohm
3. Insulation Resistance: 5Mega ohm
4. HI-Pot:300V DC/10ms

20F

SHELL		SHELL	
PIN 20	PWR	PIN 20	PWR
PIN 19	Re-PWR	PIN 19	Re-PWR
PIN 18	HPD	PIN 18	HPD
PIN 17	AUX(X)	PIN 17	AUX(X)
PIN 16	GND	PIN 16	GND
PIN 15	AUX(X)	PIN 15	AUX(X)
PIN 14	GND	PIN 14	GND
PIN 13	GND	PIN 13	GND
PIN 12	ML(X)	PIN 12	ML(X)
PIN 11	GND	PIN 11	GND
PIN 10	ML(X)	PIN 10	ML(X)
PIN 9	ML(X)	PIN 9	ML(X)
PIN 8	GND	PIN 8	GND
PIN 7	ML(X)	PIN 7	ML(X)
PIN 6	ML(X)	PIN 6	ML(X)
PIN 5	GND	PIN 5	GND
PIN 4	ML(X)	PIN 4	ML(X)
PIN 3	ML(X)	PIN 3	ML(X)
PIN 2	GND	PIN 2	GND
PIN 1	ML(X)	PIN 1	ML(X)
SPRM	Pin Description	SPRM	Pin Description

NO.	DESCRIPTION	Q'TY
1	Displayport 20P MALE CONN G/F SHELL PLATED GOLD W/LATCH	2SET
2	PVC MOLDING SSP BLUE IN COLOR	1SET
3	ABS MOLDING BLACK IN COLOR	1SET
4	Displayport 20P FEMALE CONN G/F SHELL PLATED GOLD	1SET
A		
REV.	DESCRIPTION	DATE

UNLESS OTHERWISE SPECIFIED TOLERANCE
 ANG. 0.0
 ±0.5
 ±0.3
 .00 ±0.2

SCALE: NONE UNIT: mm

DRAWN XIEBO 08/11/29

CHECKED

APPROVED

SIZE A4 REV. A

FILE NAME: ADP-DP-MF-R

PRODUCT NO.

DUN CHENG TECH. CORP.
 TEL:886-2-26739970 FAX:886-2-26739980