



NO.	ITEM	DESCRIPTION	Q'TY
1	CABLE	#26x2C+N/S+JACKET: PVC, OD:φ3.0±0.1MM UL2835 & CSA IIA/B, COLOR:BLACK	1PC
2	USB 4POS MALE CONN. ("A" TYPE) (SOLDER TYPE)	CONTACT: 5U" GOLD PLATED INSULATION: WHITE,UL94V-0 SHIELD CASE: NICKEL PLATED COVER: BLACK	1SET
3	MOTOROLA STARTAC 15POS. CONN	CONTACT: ONLY POS.4, POS.5, POS.10, POS.14. 6U" GOLD PLATED INSULATION: P.B.T+GLASS FIBER PLASTIC COVER: P.B.T+GLASS FIBER SHIELD CASE(UP & DOWN): TIN PLATED LATCH: STAINLESS SUS301	1SET
4	OUTER MOLDED	PVC, SHORE A=85±3, UL94V-0 COLOR: BLACK	7gm
5	STRAIN RELIEF	PVC SHORE A: 75±3, UL94V-0 COLOR: BLACK	3gm
6	CARBON RESISTOR	33KΩ±5%, 1/8W	1PCS
7	H.S TUBE	ID=φ1.5MM, L=6.0MM, COLOR=BLACK, UL224 ID=φ1.5MM, L=12.0MM, COLOR=BLACK, UL224	2PCS

REV.	DESCRIPTION	DATE	SIZE	REV.	FILE NAME:
A	MOTOROLA C0920 C0928 C0930 C0938 V5698 V5699 V8098 L20000 L2200 L7099 M8098 P7699 T250 P7399/T V50 V51 STARTAC130	13/05/03	A4	A	UX004NX015-S0736

P1"	WIRE COLOR	P2"
1	RED	14
4	BLACK	10
—	—	5
2,3	EMPTY	4
SHELL	NO PIN	1~3 6~9,15 11~13

UNLESS OTHERWISE SPECIFIED TOLERANCE
 ANG. ±0.5
 0, ±0.3
 .00 ±0.2

SCALE: NONE UNIT: mm

DRAWN Merry_Pang 13/05/03

CHECKED

APPROVED



DUN CHENG TECH. CORP.
 TEL:886-2-26739970 FAX:886-2-26739980

65122-LED

PRODUCT NO. UX004NX015-S0736
 DRAWN NAME: UX004NX015-S0736