



PIN ASSIGNMENT

DB 25MALE DB 9FEMALE

- | | | | |
|----|-------|---|-------|
| 8 | _____ | 1 | _____ |
| 3 | _____ | 2 | _____ |
| 2 | _____ | 3 | _____ |
| 20 | _____ | 4 | _____ |
| 7 | _____ | 5 | _____ |
| 6 | _____ | 6 | _____ |
| 4 | _____ | 7 | _____ |
| 5 | _____ | 8 | _____ |
| 22 | _____ | 9 | _____ |
| G | _____ | G | _____ |
| 1 | _____ | | _____ |

MECHANICAL:

Insulator: P B T and glass fiber reinforced (UL 94V-0).
 Contact Material: PC BOARD
 Contact Finish: Gold Over Nickel Or Tin Plated.
 Shell Finish: Steel Zinc Plated or Tin Plated.
 Hood: Molded PVC Color Beige.

ELECTRICAL:

Current Rating: 1 AMP
 Dielectric Withstanding Voltage: AC 1000V FOR 1 minute
 Insulation Resistance: 1000 M Ohm Min.(at 500v DC).
 Operating Temperature: -55°C~+105°C
 Contact Resistance: 15 m Ohm Max For 10 Sec.
 Connector Number 9 15 25 37
 Mating Force 4.6 7.7 12.7 17.7
 Unmating Force 0.4 0.5 0.8 1.2

A	ADAPTER DB9PIN FEMALE TO DB25PIN MALE W/NUT	08/05/08	APPROVED	SIZE A4	REV. A	PRODUCT NO.
REV.	DESCRIPTION	DATE	CHECKED			FILE NAME:

UNLESS OTHERWISE SPECIFIED TOLERANCE
 ANG. F0.5
 0. F0.5
 .00 F0.2

SCALE: 1:1 UNIT: mm

DRAWN ERIC 08/05/08

CHECKED

TEL:886-2-26739970 FAX:886-2-26739980

DUN CHENG TECH. CORP.

品旭-DB25M/DB9F

