


BACK SIDE

WIRE DIAGRAM:

SHELL		OVERALL BRAID	SHELL	
PIN 20	PWR	N/A	PIN 20	PWR
PIN 19	Re-PWR	ORANGE	PIN 19	Re-PWR
PIN 18	HPD	YELLOW	PIN 18	HPD
PIN 17	AUX(n)	WHITE	PIN 17	AUX(n)
PIN 16	GND	GND	PIN 16	GND
PIN 15	AUX(p)	WHITE	PIN 15	AUX(p)
PIN 14	GND	RED	PIN 14	GND
PIN 13	GND	BROWN	PIN 13	GND
PIN 12	ML3(n)	WHITE	PIN 1	ML3(n)
PIN 11	GND	WHITE DRAIN	PIN 2	GND
PIN 10	ML3(p)	WHITE	PIN 3	ML3(p)
PIN 9	ML2(n)	WHITE DRAIN	PIN 4	ML2(n)
PIN 8	GND	WHITE	PIN 5	GND
PIN 7	ML2(p)	WHITE	PIN 6	ML2(p)
PIN 6	ML1(n)	WHITE DRAIN	PIN 7	ML1(n)
PIN 5	GND	WHITE	PIN 8	GND
PIN 4	ML1(p)	WHITE DRAIN	PIN 9	ML1(p)
PIN 3	ML0(n)	WHITE	PIN 10	ML0(n)
PIN 2	GND	WHITE DRAIN	PIN 11	GND
PIN 1	ML0(p)	WHITE	PIN 12	ML0(p)
SOURCE SIDE	Pin Description	WIRE COLOR	SINK SIDE	Pin Description

NO.	DESCRIPTION	Q'TY
1	Displayport CABLE:UL20276(1P*28AWG+D+AL+MYLAR)*5C+4C*28AWG+MYLAR+AL+B DD:7.3MM	1PCS
2	Displayport CONN ASS'Y BLACK IN COLOR SHELL PLATED NICKEL W/LATCH	1SET
3	PVC MOLDED SSP BLACK IN COLOR	1SET
4		
5		1SET
A	Displayport to Displayport CABLE	
REV.	DESCRIPTION	

DATE	08/02/19	APPROVED		SIZE	A4	REV.	A	FILE NAME:	PRODUCT NO. displayport to displayport
SCALE:		UNLESS OTHERWISE SPECIFIED TOLERANCE		UNIT:					
DRAWN: eric xu		ANG: 0°		mm					
CHECKED		±0.5							
APPROVED		±0.2							



**DUN CHENG TECH. CORP.**  
TEL:886-2-26739970 FAX:886-2-26739980