



ELECTRICAL PROPERTIES:

1. 100% OPEN SHORT MIS-WIRE TEST
2. Contact Resistance: 10ohm
3. Insulation Resistance: 5Mega ohm
4. HI-Pot: 500V DC/10ms

SHELL		OVERALL BRAID	SHELL	
PIN 20	PUR	N/A	PIN 20	PUR
PIN 19	Re-PUR	ORANGE	PIN 19	Re-PUR
PIN 18	HPD	YELLOW	PIN 18	HPD
PIN 17	AUX(G)	WHITE	PIN 17	AUX(G)
PIN 16	GND	GND	PIN 16	GND
PIN 15	AUX(G)	WHITE	PIN 15	AUX(G)
PIN 14	GND	RED	PIN 14	GND
PIN 13	GND	BROWN	PIN 13	GND
PIN 12	M.3(O)	WHITE	PIN 12	M.3(O)
PIN 11	GND	DRAIN	PIN 11	GND
PIN 10	M.3(O)	WHITE	PIN 10	M.3(O)
PIN 9	M.3(O)	WHITE	PIN 9	M.3(O)
PIN 8	GND	DRAIN	PIN 8	GND
PIN 7	M.2(O)	WHITE	PIN 7	M.2(O)
PIN 6	M.1(O)	WHITE	PIN 6	M.1(O)
PIN 5	GND	DRAIN	PIN 5	GND
PIN 4	M.1(O)	WHITE	PIN 4	M.1(O)
PIN 3	M.1(O)	WHITE	PIN 3	M.1(O)
PIN 2	GND	DRAIN	PIN 2	GND
PIN 1	M.1(O)	WHITE	PIN 1	M.1(O)

NO.	DESCRIPTION	Q'TY
1	Displayport CABLE:(2F*28AWG+D+AL+MYLAR)*SC+4C*28AWG+F+MYLAR+AL+B	IPCS
2	PVC MOLDING SSP BLUE IN COLOR	ISET
3	ABS MOLDING BLACK IN COLOR	ISET
4	Displayport 20P MALE CONN G/F SHELL PLATED GOLD W/LATCH	ISET
5	Displayport 20P FEMALE CONN G/F SHELL PLATED GOLD	ISET

UNLESS OTHERWISE SPECIFIED TOLERANCE

ANG: 0.0
E: 0.5
F: 0.3
G: 0.2

SCALE: NONE UNIT: mm

DRAWN YIXIAOYANG 08/12/2

CHECKED

APPROVED

DATE 08/12/2

SIZE A4

REV. A

PRODUCT NO. DP-DP-MF-1.8MM

DUN CHENG TECH. CORP.
TEL:886-2-26739970 FAX:886-2-26739980