



**ELECTRICAL PROPERTIES:**

1. 100% OPEN SHORT MIS-WIRE TEST
2. Contact Resistance: 10ohm
3. Insulation Resistance: 5Mega ohm
4. Hi-Pot: 500V DC/10ms

SHELL	OVERALL BRAID	SHELL
PIN 20	PUR	PUR
PIN 19	Re-PUR	Re-PUR
PIN 18	HPD	HPD
PIN 17	AUX(G)	AUX(G)
PIN 16	GND	GND
PIN 15	AUX(G)	AUX(G)
PIN 14	GND	GND
PIN 13	RED	RED
PIN 12	GN	GN
PIN 11	WHITE	WHITE
PIN 10	WHITE	WHITE
PIN 9	M.3(G)	M.3(G)
PIN 8	GND	GND
PIN 7	M.2(G)	M.2(G)
PIN 6	M.1(G)	M.1(G)
PIN 5	GN	GN
PIN 4	M.1(G)	M.1(G)
PIN 3	M.1(G)	M.1(G)
PIN 2	WHITE	WHITE
PIN 1	M.1(G)	M.1(G)

NO.	DESCRIPTION	QTY
1	Displayport CABLE:(2F*28AWG+D+AL+MYLAR)*SC+4C*28AWG+P+MYLAR+AL+B	1PCS
2	PVC MOLDING SSP BLUE IN COLOR	1SET
3	PVC MOLDING SSP BLACK IN COLOR	1SET
4	Displayport 20P MALE CONN G/F SHELL PLATED GOLD W/LATCH	1SET
5	Displayport 20F FEMALE CONN G/F SHELL PLATED GOLD	1SET

REV.	DESCRIPTION	DATE	APPROVED	CHECKED	SIZE	REV.	FILE NAME:
A		08/11/29			A4	A	DP-DP-MF-R-1.8MM

UNLESS OTHERWISE SPECIFIED TOLERANCE  
 ANG. E5  
 0.0 ±0.5  
 .00 ±0.2  
 SCALE: NONE UNIT: mm  
 DRAWN YIXIAOYANG 08/11/29  
 CHECKED

**DUN CHENG TECH. CORP.**  
 TEL:886-2-26739970 FAX:886-2-26739980  
 DRAWN NAME:  
 DP-DP-MF-R-1.8MM

