

ELECTRICAL PROPERTIES:


1. 100% OPEN SHORT MIS-WIRE TEST
2. Contact Resistance: 10 ohm
3. Insulation Resistance: 5M ohm
4. Hi-POT: 300V AC/10ms

HDMI 19	HDMI 19	HDMI 19
3	3	<TMDS Data 2->
1	1	<TMDS Data 2+>
2	2	<TMDS Data 2 Shield>
6	6	<TMDS Data 1->
4	4	<TMDS Data 1+>
5	5	<TMDS Data 1 Shield>
9	9	<TMDS Data 0->
7	7	<TMDS Data 0+>
8	8	<TMDS Data 0 Shield>
12	12	<TMDS Clock ->
10	10	<TMDS Clock +>
11	11	<TMDS Clock Shield>
18	18	<+5V Power>
17	17	<Ground>
15	15	<DCC Clock>
16	16	<DCC Data>
19	19	<Hot Plug Detect>
13	13	<CEC>
14	14	

SHELL _____ SHELL

4	PVC 55P BLACK IN COLOR	1	PCS
3	MINI HDMI A FEMALE SOLDER TYPE CONN PLATED: G/F SHELL PLATED GOLD	1	PCS
2	HDMI A 19P MALE SOLDER TYPE CONN PLATED: G/F SHELL PLATED GOLD	1	PCS
1	UL20276 [(30AWG*1P+D+FAM)*4PCS+30AWG*1P+30AWG*5C] +AM+D+B	1	PCS
NO	DESCRIPTION	QTY	UNIT
A			
REV.	DESCRIPTION	DATE	

UNLESS OTHERWISE SPECIFIED TOLERANCE	ANG.	E5
	0.0	±0.5
	.00	±0.3
		±0.2
SCALE: NONE	UNIT: mm	
DRAWN: Eric	DATE: 08/11/21	
CHECKED		
APPROVED		
SIZE: A4	REV: A	
FILE NAME:	PRODUCT NO.	


DUN CHENG TECH CORP.
 TEL:886-2-26739970 FAX:886-2-26739980
 DRAWN NAME: HDMI 19 F-19M-R-L