



P1	P2
3	3
1	1
2	2
6	6
4	4
5	5
9	9
7	7
8	8
12	12
10	10
11	11
18	18
17	17
15	15
16	16
19	19
13	13
SHELL	SHELL

ELECTRICAL TEST:

1. CURRENT RATING: DC 0.5A
2. WITHSTANDING VOLTAGE: DC 300VDC
3. INSULATION RESISTANCE: 5Mohm
4. CONDUCTIVE RESISTANCE: 100ohm

5	CORE:28.5*φ16.0*φ9.5	PCS	2
4	Aluminum Alloy HOOD+Silk screen LOGO	PCS	2
3	PVC MOLDED BLACK IN COLDR	PCS	1
2	HDMI A MALE SOLDER TYPE SHELL PLATED:GOLD	PCS	2
1	HDMI CABLE UL20276 28AWG/4P+28AWG/1P+28AWG/5C+AB JACKET BLACK DD:7.0mm	PCS	1
No.	DESCRIPTION	UNIT	Q'TY
A	HDMI CABLE A-TYPE MALE TO A-TYPE MALE		
REV.	DESCRIPTION		

DATE	08/01/18	APPROVED	SIZE	A4	REV.	A	FILE NAME:	PRODUCT NO.	
UNLESS OTHERWISE SPECIFIED TOLERANCE		SCALE: NONE		DRAWN Xing Fa		CHECKED eric		DUN CHENG TECH. CORP.	
ANG: 0°		UNIT: mm		08/01/08		08/01/18		TEL:886-2-26739970 FAX:886-2-26739980	
±0.5		±0.2						HDMI-AL-XX-BK	
±0.3									
±0.2									

