



PIN ASSEMBLY

P1	P2
S1	S1
S2	S2
S3	S3
S4	S4
S5	S5
S6	S6
S7	S7
P1	P2
P2	P3
P3	
P4	
P5	P1
P6	
P7	
P8	P5
P9	
P10	
P11	P2
P12	
P13	
P14	
P15	

ELECTRONIC TEST:
 1.OPEN/SHORT/INTERMITTE:100%.
 2.INSULATION RESISTANCE:5MΩ.
 3.CONTACT RESISTANCE:10Ω.
 4.HI-POT:300V 10ms

3	PVC SSP MOLD COLOR: BLACK	PCCS	1
2	SLIMLINE SATA 7+6PIN CABLE SIDE	PCCS	1
1	SLINLIN ATA 22PIN CABLE SIDE	PCCS	1
NO.	DESCRIPTION	UNCT	Q'TTY

REV.	DESCRIPTION
A	

UNLESS OTHERWISE SPECIFIED TOLERANCE

ANG: F30
 0.0 ±0.5
 .00 ±0.2

SCALE: 1:1 UNIT: M/M

DRAWN XIEBO 09/02/05

CHECKED ERIC 09/02/05

APPROVED

DATE 09/02/05



DUN CHENG TECH. CORP.
 TEL:886-2-26739970 FAX:886-2-26739980

DRAWN NAME: SATA22C-SLIMS13C

PRODUCT NO.

FILE NAME: