



ELECTRICAL TEST:

100% OPEN SHORT MIS-WIRE TEST
 CONTACT RESISTANCE: 20HM MAX
 INSULATION RESISTANCE: 5MEGA OHM MIN
 HIPDT TEST: DC300V 10MS

10	PVC MOLDED COLOR:GRAY		
9	HEAT SHRINK TUBING	1	PCS
8	HEAT SHRINK TUBING	1	PCS
7	4.79*1.9MM #4-40 NUT	4	PCS
6	SCREW #4-40 L: 8MM	4	PCS
5	USB MARK	1	PCS
4	?? ????(?PORT USB)	1	PCS
3	HOUSING	1 & 8	PCS
2	USB A-TYPE FEMALE WHITE PASTERN GOLD FLASH	2	PCS
1	UL2725 28#/1P+24#/2C+AEB DD:4.7MM REV:2.0 COLOR: GRAY	2	PCS
ND.	DESCRIPTION	Q'TY	UNIT

USB P1	HOUSING	USB P2	HOUSING
1	廠	1	廠
2	啞	2	啞
3	鄭	3	鄭
4	筐	4	筐
shell	shield	shell	shield

UNLESS OTHERWISE SPECIFIED TOLERANCE ANG: 0, ±0.5 ±0.3 ±0.2

SCALE: NONE UNIT: mm

DRAWN My.Chen 01/22/05

CHECKED

APPROVED

DATE 01/22/05

SIZE A4 REV. A

PRODUCT NO. USB2-AF2HS-016

FILE NAME: USB2-AF2HS-016

立發 USB2-AF2HS-016

DUN CHENG TECH. CORP.
 TEL:886-2-26739970 FAX:886-2-26739980