



USB-A MALE

FUJI 14 PIN

Pin Assembly

USB-A MALE

FUJI 14 PIN

- 1** ----- RED 28 AWG ----- **8**
- 2** ----- WHITE 28 AWG ----- **14**
- 3** ----- GREEN 28 AWG ----- **11**
- 4** ----- BLACK 28 AWG ----- **4**
- G** ----- DRAID WIRE ----- **G**

ELECTRONIC TEST:

- 1. OPEN/SHORT/INTERMITTE: 100%.
- 2. INSULATION RESISTANCE: DC 250V AT 10ms R > 10M Ω
- 3. CONTACT RESISTANCE: < 5Ω.

6	CORE: φ12*25*φ5.6mm	1	PCS
5	MINI USB FUJI 14PIN CONNECTOR CONTACT PLATED: G/F(FUJI)	1	PCS
4	PVC MOLDED BLACK IN COLOR		
3	UL2725 28#*1P+28AWG*2C+ADB REV:2.0 BLACK IN COLOR OD:3.5mm	1	PCS
2	PVC MOLDED BLACK IN COLOR	1	PCS
1	USB A TYPE MALE SOLDER TYPE CONNECTOR INSULATOR WHITE COLOR	1	PCS
NO	DESCRIPTION	QTY	UNITS
A	USB-A MALE/FUJI 14P MOLDED/ASSY CABLE		
REV.	DESCRIPTION	DATE	

07/02/14	APPROVED	SIZE	REV.	FILE NAME:
	CHECKED	A4	A	USB2-FUJI-14P-183-C
<p>UNLESS OTHERWISE SPECIFIED TOLERANCE</p> <p>ANG: F3</p> <p>0 ±0.5</p> <p>.0 ±0.3</p> <p>.00 ±0.2</p>				
<p>SCALE: NONE UNIT: mm</p> <p>DRAWN ERIC XU 07/02/14</p> <p>CHECKED</p>				
<p>DUN CHENG TECH. CORP.</p> <p>TEL: 886-2-26739970 FAX: 886-2-26739980</p> <p>DRAWN NAME:</p>				

