



USB-A MALE

8 PIN FEMALE

Pin Assembly

USB-A MALE 8 PIN FEMALE

- 1** ---- RED 24 AWG **1**
- 2** ---- GREEN 28 AWG **6**
- 3** ---- WHITE 28 AWG **7**
- 4** ---- BLACK 24 AWG **8**
- G** ---- DRAID WIRE **G**

ELECTRONIC TEST:

- 1.OPEN/SHORT/INTERMITTE:100%.
- 2.INSULATION RESISTANCE:DC 250V AT 10ms R>10MΩ
- 3.CONTACT RESISTANCE:<5Ω.

| | |
|----------|-------|
| " L " | |
| 20285-6 | 6 ft |
| 20285-10 | 10 ft |

| | | | |
|------|---|------|-------|
| 6 | 8 PIN FEMALE CONNECTOR | 1 | PCS |
| 5 | PVC MOLDED BLACK IN COLOR | 1 | SET |
| 4 | UL2725 28#*1P+28AWG*2C+ADB REV:2.0 BLACK IN COLOR OD:3.5 | | |
| 3 | FERRITE CORE L25mm*ID05.6*OD012mm | 1 | PCS |
| 2 | PVC MOLDED BLACK IN COLOR | 1 | PCS |
| 1 | USB A TYPE MALE SOLDER TYPE CONNECTOR INSULATOR WHITE COLOR | 1 | PCS |
| NO | DESCRIPTION | Q'TY | UNITS |
| A | USB-A MALE/8 PIN FEMALE MOLDED/ASS'Y CABLE | | |
| REV. | DESCRIPTION | DATE | SIZE |

| | | |
|--|---------------------------------------|--|
| <p>UNLESS OTHERWISE SPECIFIED TOLERANCE</p> <p>ANG. 0.</p> <p>F0.5 ±0.5</p> <p>F0.2 ±0.2</p> <p>SCALE: NONE</p> <p>DRAWN Money_XU</p> <p>CHECKED</p> <p>APPROVED</p> | <p>UNIT: mm</p> <p>DATE: 06/03/03</p> | <p>DUN CHENG TECH. CORP.</p> <p>TEL:886-2-26739970 FAX:886-2-26739980</p> |
| <p>PRODUCT NO. 20285-XX</p> <p>FILE NAME: 20285-XX</p> | <p>DATE: 06/03/03</p> | <p>PRODUCT NAME: USB2-NIKON-183</p> |