



ELECTRONIC TEST:
 1.OPEN/SHORT/INTERMITTE:100%.
 2.INSULATION RESISTANCE:20M Ω .
 3.CONTACT RESISTANCE:3 Ω .
 4.HI-POT:500V DC/10MS.

6	CORE: $\phi 12*25*\phi 5.6mm$	PCS	1
5	MICRO USB A TYPE MALE SHELL PLATEDNICKEL CONTACT:G/F	PCS	1
4	PVC MOLDED BLACK IN COLDR		
3	CABLE: 1P*28AWG+2C*26AWG+AL+D+B DD3.8 BLACK IN COLDR REV:3.0		
2	PVC SSP MOLDED BLACK IN COLDR		
1	USB-A TYPE MALE SHELL PLATEDNICKEL CONTACT:G/F	PCS	1
NO.	DESCRIPTION	UNIT	QTY
A	USB-A MALE/MINI USB MISTUMI MALE MOLDED CABLE		07/1/9
REV.	DESCRIPTION	DATE	

Pin Assignment

USB AM	SIGNAL NAME	COLOR	MICRO USB A
1	VBUS	RED	1
2	D-	WHITE	2
3	D+	GREEN	3
	ID	<RA_PLUG_ID	4
4	GND	BLACK	5
	SHELL SHIELD	DRIAN	SHELL

UNLESS OTHERWISE SPECIFIED TOLERANCE
 ANG: 0°
 F0.5
 F0.3
 F0.2
 SCALE: NONE UNIT: mm
 DRAWN erix cu 07/1/9
 CHECKED / /

DUN CHENG TECH. CORP.
 TEL:886-2-26739970 FAX:886-2-26739980
 DRAWN NAME: USB3-AMMUA-180-C
 PRODUCT NO.



APPROVED / /
 SIZE A4 REV. A
 FILE NAME: